





IPFBoc

OB

LARGE-FORMAT SOLUTIONS

INTRODUCING THE 44-INCH imagePROGRAF iPF8000 PRINTER, THE MOST RECENT ADDITION TO CANON'S LATEST GENERATION OF LARGE-FORMAT PRINTERS.

Canon unveils the new imagePROGRAF iPF8000 printer, the next step in redefining large-format printing and the best solution for any color professionals needs.



imagePROGRAF® iPF8000

The new imagePROGRAF iPF8000 printer is the total creative solution for any color professional looking for impressive, full-bleed color output, strength in paper handling, and exceptional speed. The iPF8000 printer features the newly developed 12-color pigment ink system with LUCIA[™] inks designed to expand the spectrum of shades in order to produce outstanding colors, neutral and stable grayscales, as well as incredible tonal detail.

The integration of speed and quality is attained with two of Canon's latest and strongest technological achievements– the L-COA controller and the dual print-head system. The Canon L-COA controller is dedicated to the imagePROGRAF printer and is designed to optimize the best quality output at the highest possible speeds. The iPF8000 printer is designed for reliability, simplicity, productivity and, above all, quality.

REDEFINING LARGE-FORMAT PRINTING

An absolute creative solution-

brilliant color, exceptional speed, and maximum productivity

EXQUISITE COLOR

The imagePROGRAF iPF8000 printer features a 12-color pigment ink system designed to produce a wide color gamut that expands the range of color reproduction and enhances color purity substantially. The dramatically expanded color gamut produces the most outstanding, pure, exquisite colors to accurately match a larger spectrum of colors. Black and matte black, plus two levels of gray, produce monochrome prints that surpass all expectations. The two levels of gray reduce graininess, metamerism, and virtually eliminate color shifts. There's ease in printing on various substrates, such as gloss or matte, due to the automatic switching between black and matte black, which helps increase productivity and reduce operating expenses.

EXTRAORDINARY SPEED AND OUTSTANDING PRODUCTIVITY

The imagePROGRAF iPF8000 printer is built around Canon's innovative L-COA (Large-format printer COmmon Architecture) controller, a highly advanced system processor that dynamically optimizes output speed and print quality based on the type of image being printed and the media used. It's so advanced, yet so simple. Vivid, breathtaking, long-lasting prints are achieved by combining Canon's advanced technological achievements –a single chip alongside two high-density one-inch print-head systems with FINE technology. Every printer looks for accuracy, productivity, and reliability– all of which are packed into this 44" printer.

BUNDLED SOFTWARE

The imagePROGRAF iPF8000 printer comes equipped with an array of software applications that expand the printer's capabilities and simplify its use in busy environments. Exquisite, stunning prints can be created right out of the box, with software that's just as innovative as the print itself.

■ **Print Plug-in for Photoshop**[®] – Allows for 16-bit image processing to dramatically improve gradations and image quality.

Digital Photo Print Pro – Eliminates red-eye, improves skin tones, removes moiré, makes image corrections to digital photos with a click of a button, and also includes templates for creating calendars.

PosterArtist – PosterArtist helps users of all levels to create professional-looking posters, banners, and signage with complete ease.

Printer Driver 2006 – The imagePROGRAF printer driver 2006 works with both Windows® and Macintosh® operating systems, offering exceptional, high-quality prints through easy usability and accurate color. Features such as Free Layout and Canon imageRUNNER® Scan-to-Print are included.





06), User Software CD, User Manual CD,

Quick Reference Guide, Quick Start Guide,

PosterArtist CD Disk 1 and Disk 2, Digital

Photo Print Pro CD, LFP Specialty Media

Swatch Book, Tools to Assemble the

• Durable Banner (Polypropylene),

Banner Vinyl (Scrim), Tyvek Banner,

Removable Banner Vinyl, Adhesive

Matte Vinyl, Durable Backlit Film,

Photographic Paper, Heavyweight Glossy Photographic Paper,

Heavyweight Satin Photographic

Paper, Premium RC Photogloss,

RC Photo Luster

Proofing Paper

Premium Matte Pape

Proofing Paper

Fine Art Paper

Matte Par

Premium RC Photomatte, Premium

• Commercial Proofing Paper, Premium

• Universal Bond Paper, Matte Coated,

Paper, Heavyweight Coated Paper,

Heavyweight Matte Coated Paper.

Fine Art Photo Rag, Fine Art German

Etching, Fine Art Enhanced Velvet, Fine Art Watercolor Paper, Fine Art

Smooth Rag, Fine Art Smooth Rag

Water-Resistant Canvas, Graphic

Matte Canvas, Canvas Semi-Glossy

Heavyweight, Fine Art Smooth Natural Rag, Fine Art Textured Rag, Fine Art

Paper, Premium Bright Photo Glossy Paper, Premium Bright Photo Satin

Back Print Back Lit Film

Photo PaperPremium Super-Gloss, Glossy

Photographic Paper, Satin

Stand, Warranty.

MEDIA TYPES

Signage Media

SPECIFICATIONS

MAIN UNIT

- Print Head (PF-02)
- Technology · FINE (Full-Lithography Ink-Jet Nozzle Engineering)
- Configuration
- 6 Colors per Print Head
- Two Print Heads (Total 12 Colors) - Print Head (L) Y/PC/C/PGY/GY/MBK
- Print Head (R) PM/M/BK/R/G/B
- Replacement - End-User Replaceable
- Number of Nozzles
- 2,560 Nozzles per Color
- 30,720 Nozzles Total Droplet Size
- Uniform 4 Picoliter for All Colors
- Nozzle Pitch (Head Resolution)
- 1200 dpi
- **Print Head Swath** 1.07'
- Print Resolution (Max.) • 2400 x 1200 dpi
- Ink Tv
- LUCIA Ink (Pigment-Based)
- **Replacement Ink Tank**
- PFI-701 (700ml) or PFI-301 (330ml) Colors
- Cyan, Photo Cyan, Magenta, Photo Magenta, Yellow, Black, Matte Black, Red, Green, Blue, Gray, Photo Gray
- Ink Tank Shipped with the Printer • PFI-301 x 12 Colors (Full 330ml
- Each Color)
- Ink Supply Method • Tubing System with Sub-Tanks for
- Continuous Ink Supply
- Nozzle Recovery System
- Non-Firing Nozzle Detection and Compensation

Maximum Media Roll Outer Diameter • 5.9" (150mm)

- **Bundled Software**
- Printing Software
- Printer Driver 2006, Print Plug-in for Photoshop,** Printer Driver Extra (Free Layout, imageRUNNER Linking Function)
- Applications - PosterArtist 2006,[†] Digital Photo Print Pro[†]
- Utilities
- GARO Status Monitor with SMTP E-mail Printer Status Notification, Media Configuration Tool, Remote UI
- Printer Languag
- GARO (Canon Proprietary)
- Operating System^{††} Windows 98SE/ME/2000/XP/2003 ServerVista, *** Macintosh OS 9.1/X 10.2/ 10.3/10.4 (Power PC or Intel® Processors)
- Interface (20.28"/515mm), A1 (23.38"/594mm), A0
 - Standard - USB 2.0 High Speed
 - 10/100Base-T/TX Optional
 - IEEE1394 (FireWire) Acoustic Noise
 - Operation
 - 54dB or Less
 - Standby
- 2" (3" Core With Optional 3" Core Spool) 35dB or Less
 - Acoustic Power (Operation and Standby) - 6.9 Bels or Less Power Supply

AC 100 – 240V (50 – 60Hz)

- Power Consumption Leading and Left/Right Edges: 0.20"
- Maximum (5mm), Trailing Edge: 0.90" (23mm)
 - 190W or Less
 - Standby (100 120V) 5W or Less (8W or Less when EB-05
 - is Installed)

- Power Off (Standby, 100 120V) - Less than 1W (Compliant with Executive Order)
- Certification Electrical Safety Regulations
- UL (USA), C-UL (Canada), S mark (Argentina), CB Certification (Others)
- Electromagnetic Interface Regulations FCC Class B (USA), IC Class B (Canada)
- Environmental Certifications
- ENERGY STAR[®] (World Wide). RoHS Directive, WEEE, Executive Order (USA)
- **Operational Environment**
- Temperature - 59 - 86 F° (15 - 30 C°)
- Relative Humidity - 10 - 80% (Condensation Free)
- sions with Stand (H x W x D) • 45.0" x 74.5" x 38.4" (1,144 x 1,893 x
- 975mm) Weight with Stand
- Approx. 313 lb. (142kg)
- Package Dimensions (H x W x D)
- 48.3" x 81.9" x 41.7" (1,226 x 2,080 x 1,060mm)
- Package Weight (Including Pallet)
- Approx, 499 lb. (226kg) **User Replaceable Items**
- Ink-Tank PFI-301/PFI-701
- Print Head (PF-02)
- Maintenance Cartridge (MC-08) • Durable Rotary Media Cutter (CT-06)
- Option
- IEEE1394 Expansion Board (EB-05)
- Automatic Media Take-Up Unit (TU-06)
- 2" Core Roll Holder (RH2-43)
- 3" Core Roll Holder (RH3-43) What's In The Box

Printer, Stand with Basket, Power Cord, Two Print Heads (6 Colors per Print Head) 12 PFI-301 Ink Tanks (12 Colors x 330ml), Preinstalled Maintenance Cartridge (MC-08), Preinstalled Rotary Media Cutter (CT-

* The maximum printable length varies depending on the application, OS, and RIP used. The maximum printable length from Printer Driver is 50 feet.

** For Adobe® Photoshop 6, 7, CS, and CS2 running on Windows 2000/XP or Macintosh OS 9.1 or OS X 10.2/10.3/10.4 (Power PC or Intel Processor)

*** Windows 2000/XP/2003 Server, Auto Layout and imageRUNNER Linking Function for Macintosh OS 10.2.8 or later.

Printer Controller

L-COA Controller

One Roll, Front-Loading, Front Output

One Sheet, Front-Loading, Front

Printer Memory • 384MB

Media Feed

• Roll Feed

Cut Sheet

Output

• 8" - 44" (Cut Sheet)

• 10" - 44" (Roll Feed)

Maximum Print Length

- 63" (1.6 Meters)

- 59 Feet (18 Meters)*

Borderless Printing Width

• 10", 14", 16", 24", 36", 42", B2

• User-Replaceable Durable Rotary

• 0.07mm - 0.8mm (2.8 mil-31.4 mil)

• Basket (Standard), Automatically

All Sides: 0.20" (5mm) or 0" for

Winding Media Take-Up Reel (Optional)

(33.11"/841mm). B0 (40.55"/1.030mm)

(Roll Media Only)

Media Cutter

Blade (CT-06)

Media Thickness

Media Core Sizes

Printable Margins

Borderless

• Manual Feed (Top/Front)

Media Output

Roll Feed

um Media Length

Media Width

• 8" (203mm)

• Manual Feed

Minim

Roll

- t Windows 2000/XP
- th For imagePROGRAF Printer Driver. For printing from PostScript® applications such as Adobe Illustrator® or QuarkXPress®, please use a PostScript
- compatible RIP package. For a list of Canon recommended RIP packages, please refer to Canon Alliance and Industry Marketing program list of RIP vendors.
- ttt Available 2007



1-800-OK-CANON www.usa.canon.com

Canon U.S.A., Inc. One Canon Plaza Lake Success, NY 11042








PRINTED ON RECYCLED PAPER IN THE U.S.A.

1206-iPF8000-25M-LTM



United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All referenced product names and other marks are trademarks of their respective owners.

Specifications and availability are subject to change without notice. ©2006 Canon U.S.A., Inc. All rights reserved.

0068W630